

## GRANT OF EQUIPMENT AUTHORIZATION



Certification Issued Under the Authority of the Federal Communications Commission

By:

Timco Engineering, Inc. 849 NW State Road 45 <BR>P.O. Box 370, Newberry, FL 32669 Date of Grant: 10/20/2016

Application Dated: 10/20/2016

Pycom Ltd Registered Office 57 Avenue Road Cranleigh, Surrey GU6 7LJ UK UK, United Kingdom

## **Attention: Daniel Campora**

Grant Notes

## NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER:	2AJMTL	.OPY1R			
Name of Grantee:	Pycom L	td			
Equipment Class: Notes: Modular Type:	Digital Tr LoPy Single M	ransmission Syster odular	n Lillion		
FCC Rule Parts	Ê	Frequency Range (MHZ)	Output Watts	Frequency Tolerance	Emission Designator
15C	do	2402.0 - 2480.0	0.0023	dir.	
15C	194	2412.0 - 2462.0	0.0893	- 40x	
15C	AQ.	903.0 - 914.2	0.0914	> VA	
	VA LUN I	F 100	121 1	Wh Wh	

Single Modular Approval. Power listed is conducted. Approval is limited to OEM installation only. Compliance of this device in all final host configurations is the responsibility of the Grantee. This device is to be used only for mobile and fixed applications. The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20cm from all persons and must not transmit simultaneously with any other antenna or transmitter or in accordance with FCC multi-transmitter product procedures. OEM integrators must be provided with antenna installation instructions and labeling requirements for finished products. OEM integrators and end-Users must be provided with transmitter operation conditions for satisfying RF exposure compliance. This grant is valid only when the device is sold to OEM integrators and the OEM integrators are instructed to ensure that the end user has no manual instructions to remove or install the device. Separate approval is required for all other operating configurations, including portable configurations with respect to 2.1093 and different antenna configurations. This device has 20 and 40 MHz bandwidth modes.